

- Made from 100% Recycled Material
- Size 5'x5' or 5'x8' Sheets
- 1/4" thick
- Homogeneous PVC
- 8 Colors
- 3 Textures (*Standard, Ripple and Texture*)
- All Seams Heat Welded
- Slip Resistance 88 dry and 92 wet
- **Made in the USA**
- We provide all needed accessories



Color Chart & Surface Options

Color Chart (Colors available in gloss or matte finish)



Blue



Burgundy



Black



Dark Gray



Green



Light Gray



Tan



Terra Cotta



Brown

Coefficient of Friction Standard:
ADA Recommends a minimum
60 C.O.F. on flat dry surfaces
50 C.O.F. on flat wet surfaces

Do you have Quarry Tile?

Installed Cost per square foot: \$8.00 to \$13.00

Coefficient of Friction: Dry 70 Wet 60

Pros: Some versions are Inexpensive, Class A fire rating

Cons: Porous, Will absorb odors in seafood/Deli area, Grout issues/repairs, Slippery, Hard to clean, Hard surface is rough on employees body's and creates fatigue, Supports the growth of bacteria and mold, Loud & no noise reduction properties

Do you have Epoxy/Resinous Flooring?

Installed Cost per square foot: \$5.00 to \$20.00

Coefficient of Friction: Dry 70 Wet 55

Pros: Some versions are inexpensive, Multi color options

Cons: Slippery, Stains easy, Cracks, Is only water proof for short period of time then will allow seeping, If aggregate is used for slip resistance floor is hard to clean, hard surface is rough on employees body's and creates fatigue, Expensive to install, loud & no noise reduction properties, dangerous chemical vapors when being installed and foul odor.

